

Data sheet  
**SPARK**



## GENERAL

Art. no.:	A-056	E-class number:	40-02-01-06
EAN:	4030281010913	Customs no.:	84798997
Standard:	EN 12841-C:2006 EN 15151-1:2012 EN 341-2A:2011		

## Data sheet

### SPARK

SPARK is designed for permanent use in the toughest conditions. The product combines the advantages of the best descenders for industrial and rescue use. SPARK is characterised in particular by its design without anti-panic function, which enables fast, precise and uninterrupted abseiling.

Intuitive and simple rope handling, while the carabiner on the harness can remain connected to the device, the well thought-out ergonomics and the precise operation of the lever allow for the best handling. Thanks to the sophisticated rope guide inside the device, the rope is protected against twisting and kinking as well as heavy wear.

- Fast, precise, uninterrupted abseiling without anti-panic-function
- Outstanding handling thanks to compact, ergonomic design and intuitive rope guide
- Durable and robust: 100% metal without vulnerable plastic parts

#### FEATURES

Abseiling speed:	2,00 m/s
Fall indicator	
Max. service life:	30 Years
Rated load:	250
Temperature:	from 60 °C to -30 °C

#### DIMENSIONS

Size:	47x79x175mm
Weight:	0,51 kg

#### MATERIAL

Material:	Aluminium, Steel
-----------	------------------